

# PJ759

**LIGHT, BRIGHT AND  
PORTABLE PROJECTOR**  
WITH KEYSTONE CORRECTION

## Versatile performance leader.

The ViewSonic® PJ759 projector is a performance leader with a rich feature set at an affordable price. The PJ759 delivers 2,600 LUMENS AND 1024x768 XGA RESOLUTION, scalable up to 1600x1200 UXGA, for crisp, detailed images in any lighting situation. With SEVEN PICTURE MODES, including daylight, blackboard, whiteboard and greenboard, you can adjust the light output for any given environment. This multimedia projector is easy to set up and its DIRECT OFF FEATURE allows you to unplug it and go. The built-in 7 watt speakers and wide array of PC AND VIDEO CONNECTIVITY OPTIONS let you deliver dynamic, versatile presentations. The easy lamp and filter replacement make maintenance a breeze. The PJ759 is ideal for table-top or mounted use in the office, classroom or on the road.



### PORTABLE WITH EASY SET UP

- > **Bright in virtually any setting**  
Packs 2,600 lumens in 7.8 pounds. It's the bright choice for mobile presenters.
- > **Quick set up**  
Auto vertical keystone correction automatically squares the image for quick set up. The direct off feature lets you just unplug the projector and go.
- > **Enhanced security features**  
Security bar and user-assigned PIN code protect your projector from theft and unauthorized use.
- > **Ultimate display source flexibility**  
With two RGB inputs you can connect a computer or add a video source for dynamic meetings and presentations.
- > **Easy maintenance**  
The sliding filter cover and simple lamp replacement from the top of the unit make maintenance a breeze.
- > **Whisper-mode extends lamp life and reduces noise output**
- > **Customize start-up with MyScreen**  
Allows the user to personalize the start-up screen image by adding your company logo or a favorite photo.
- > **The best warranty in the business**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# PJ759

## LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH KEYSTONE CORRECTION



<b>PROJECTOR</b>	Type	0.63 Poly-Si TFT with micro-lens
	Pixel Format	1024x768 XGA
	Lens	Manual zoom, manual focus
	Zoom Factor	1.2
	Keystone	Vertical $\pm 30^\circ$
<b>DISPLAY</b>	Size	30"–300" (diagonally)
	Throw Distance	35"–354"
	Throw Ratio	1.5–1.7:1
	Lamp	220W, 2,000 hrs. normal, up to 3,000 hrs. whisper-mode*
	Brightness (max)	2,600 ANSI lumens
<b>AUDIO</b>	Speakers	1x7W
	<b>INPUT SIGNAL</b>	Video
<b>COMPATIBILITY</b>	Frequency	$F_H$ : 31~106kHz, $F_V$ : 56~120Hz
	PC	Analog: from VGA up to UXGA (scaled)
<b>CONNECTOR</b>	Mac®†	Analog: up to UXGA
	RGB (input)	15-pin HD, D-sub (2)
<b>POWER</b>	Composite Video (input)	RCA jack (1)
	S-video (input)	Mini-Din 4-pin
	Component Video (input)	VGA DB-15 to component adapter**
	Audio (input/output)	Stereo mini-jack 1-in, 1-out
<b>USB</b>		For mouse control only
<b>CONTROLS</b>	Voltage	100–240VAC, 50–60Hz (universal)
	Consumption	320W (typ)
<b>OPERATING CONDITIONS</b>	Basic	Standby, input, reset, V. keystone
	OnView®	Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. phase, H. size, auto adjust, video NR, color space, component, video format, frame lock, computer in, resolution, auto keystone, information, V. keystone, whisper, mirror, volume, speaker, audio, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, source name, auto search, auto on/off, lamp time, filter time, My Button, service menu, security
<b>NOISE LEVEL</b>	Temperature	41–95°F (5–35°C)
	Humidity	10–85% (non-condensing)
<b>DIMENSIONS</b>	Altitude	0–60,000 ft+
	Normal	36 dB (typ)
<b>WEIGHT</b>	Whisper-mode	30 dB (typ)
	Physical (W x H x D)	13.4" x 3.9" x 10.6" (340mm x 100mm x 270mm)
<b>REGULATIONS</b>	Net	7.8 lb. (3.5 kg)
	Gross	17.0 lb. (7.7 kg)
<b>OTHER</b>	UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S	
	Short throw, auto vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control, direct off, low noise (30 dB), unplug and go, white board, black board, green board, daylight mode, adjustable fan speed	
<b>WARRANTY</b>		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp***



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Running whisper-mode exclusively can extend lamp life. \*\*Optional cables required. \*\*\*Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13641-01B-09/07] PJ759-1

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)